Brake Calipers EV 028 FEM and EH 028 FEM

RINGSPANN[®]

spring activated - electromagnetically released




Advantages

The brake caliper EV 028 FEM or EH 028 FEM is a very compact and high efficient disc brake with very low power consumption. Its floating bearing compensates small misalignments of the brake disc. The attached electronic reduces the power consumption in open position automatically.

Options

- Available with cCSAus approval
- Inductive proximity switch: "Brake released"-, "Brake closed"-status and/or "Friction block wear adjustment necessary"



Technical Data

	Brake Calipers EV 028 FEM and EH 028 FEM with supply voltage		
	220 to 240 VAC	380 to 480 VAC	
Brake disc diameter	Braking torque	Braking torque	
mm	Nm	Nm	
300	940		
355	1 160		
430	1 460		
520	1 820		
630	2 260		
710	2 580		
Clamping force	10000 N		
Clamping force or braking torque adjustable	60 - 100%		
Power consumption	15 W	19 W	
in open position	(100% duty factor)		
Power when opening the brake (< 1 s)	1 850 W	2 500 W	
Fuse rating	10 A, Type "B"		
Max. number of actuation	360/h permanent activations at 20° C ambient temperature		
Actuation frequency*	at least 8 seconds between 2 activations		
Weight	24 kg		
The braking torques shown in the diagram are based on a			

The braking torques shown in the diagram are based on a theoretical friction coefficient of 0,4.

* Shorter actuation frequency on request

Features	Code	
Brake Caliper with electromagnet	E	
Mounting to the machine parallel or at right angles to the brake disc		
Frame size 028	028	
Spring activated	F	
Electromagnetically released		
Manual adjustment to accommodate friction block wear		
Supply voltage 220 to 240 VAC Supply voltage 380 to 480 VAC		
Electromagnet mounted in central position		
Thickness of brake disc 10 16 mm or 18 26 mm	12 25	

Example for ordering

Brake Caliper EV 028 FEM, supply voltage 400 VAC, Electromagnet mounted in central position, thickness of brake disc 15 mm:


EV 028 FEM - 480 M - 12

Brake Calipers EV 028 FEM and EH 028 FEM

RINGSPANN[®]

spring activated – electromagnetically released

Brake Caliper EV 028 FEM



Brake Caliper EH 028 FEM

